A NEW STANDARD IN CONNECTIVITY.

Exceed homebuyers expectations with Wi-Fi® Garage Door Openers from LiftMaster®.



BUILDER BROCHURE

GARAGE DOOR OPENERS/GATE OPERATORS/ ACCESS CONTROL



TESTED TO TWO LIFETIMES.

LiftMaster® Garage Door Openers provide the durability your homebuyers demand.

LiftMaster Garage Door Openers are subject to over 50 different tests, through 50,000 cycles. That's two lifetimes for a standard garage door opener, so you can spec them into any home with total confidence.



OUALITY GUIDES EVERYTHING WE DO.

LiftMaster is a brand that people can trust and a partner that professionals can rely on. Our commitment to continuous improvement motivates us to exceed customers' evolving expectations.

"IF I DIDN'T TRUST IT IN MY OWN HOME,
I WOULDN'T INSTALL IT IN SOMEONE ELSE'S."
—ED BROWN

When you choose LiftMaster, you can be confident that the door will open and close without issues well beyond your warranty period—so homebuyers have a positive experience with your business.



Builder
2012-2019

A LEGACY OF RECOGNITION.

For the eigth consecutive year, LiftMaster has been proudly voted the #1 garage door opener brand preferred by builders.*

myQ ° COMPLETES THEIR SMART HOME.

Smart-home connectivity has an important role in the ever-evolving residential world.

Nearly a third of U.S. broadband households own a connected device in their home. These days, residents increasingly seek out the latest technology to experience home safety, security and convenience like never before.



CLOSE YOUR GARAGE DOOR FROM ANYWHERE. OPEN IT FOR ANYONE. GET ALERTS.

LiftMaster® offers built-in Wi-Fi with the majority of its garage door openers,* providing homeowners with smartphone integration. myQ Family Share allows homeowners to invite up to three additional people to access the same myQ account without having to share a password. With myQ Family Share your home buyer's inner circle has the ability to view and control myQ connected devices, including garage door openers, gates and lights.

FREE IN-GARAGE DELIVERY

Now available to millions^{††} of Amazon Prime members

Only LiftMaster professionally-installed garage door openers are compatible with Key by Amazon, allowing Prime members to have packages delivered securely right inside the garage.

To see how it works, visit LiftMaster.com/KeyForBuilders





myQ integrates with leading smart home platforms. Visit myQ.com to learn more.



LiftMaster 8010 will need an Internet Gateway to connect with Wi-Fi.

Requires purchase of myQ Home Bridge 819LMB.

- * Linking myQ to partner app may require accessory purchase or subscription fee after 30-day trial.
- ** https://www.cnet.com/videos/what-do-millennials-want-in-a-smart-home/
- *** Smartphone not included. Application screens may vary. Cellular data or Wi-Fi connection required.
- † Test equipment regularly and follow safety instructions.
- †† *In-Garage Delivery is available for Amazon Prime members in select cities and surrounding areas.

RESIDENTIAL ACCESS SOLUTIONS COMPARISON CHART.

	8500W	8500	WLED	8550WLB	8587W	8360WLB	8355W
		1				a	6
	DC Battery Backup Wall	DC Battery Backup	E SERIES® DC Battery Backup Belt	DC Battery Backup	3/4 HP AC	PREN DC Battery Backup	IUM SERIES 1/2 HP AC
Description	Mount Wi-Fi®	Capable Wall Mount	Drive LED Wi-Fi	Belt Drive Wi-Fi	Chain Drive Wi-Fi	Chain Drive Wi-Fi	Belt Drive Wi-Fi
Built-in Wi-Fi	Yes	-	Yes	Yes	Yes	Yes	Yes
myQ [®] Connectivity	Yes	Yes	Yes	Yes	Yes	Yes	Yes
California SB-969 Compliant**	Yes	-	Yes	Yes	-	Yes	-
Security+ 2.0°, Tri-Band Radio (310, 315 and 390 MHz), Electronic Limit/Auto-Force	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Battery Backup	Yes 485LM Battery Included	Capable 475LM Battery	Yes 485LM Battery Included	Yes 485LM Battery Included	-	Yes 485LM Battery Included	-
Garage Door Lock	841LM - 1 included (2 max)	Automatic deadbolt lock included *	841LM capable (2 max)	841LM capable (2 max)	841LM capable (2 max)	841LM capable (2 max)	-
Lighting	827LM myQ Remote LED Light, 1,500 Lumens	380LM Remote Light, 2 x 100 Watts	LED, 3,100 Lumens	Side to Side, 2 x 100 Watts	Side to Side, 2 x 100 Watts	Front to Back, 2 x 100 Watts	Front to Back, 2 x 100 Watts
Soft Start/Stop	Yes	Yes	Yes	Yes	-	Yes	-
Timer-to-Close	Yes	Yes	Yes	Yes	Yes	-	-
Rail	-	-	T-Rail System	T-Rail System	I-Beam Rail System, 2-Speed Sprocket, Sensor Extension Brackets, Chassis Support Bracket	T-Rail System	T-Rail System
Control Panel	880LMW Smart Control Panel®	889LM myQ Control Panel	880LMW Smart Control Panel	880LMW Smart Control Panel	880LMW Smart Control Panel	886LMW Motion Detecting Control Panel	882LMW Multi-Function Control Panel®
Motion Detection Light Activation	Yes	Yes	Yes	Yes	Yes	Yes	-
LCD Programming Menu	Yes	-	Yes	Yes	Yes	-	-
Maintenance Alert System	Yes	-	Yes	Yes	Yes	Yes	Yes
Packed-In Accessory	893MAX 3-Button Remote Control	893MAX 3-Button Remote Control	893MAX 3-Button Remote Control	893MAX 3-Button Remote Control	893MAX 3-Button Remote Control	893LM 3-Button Remote Control	893LM 3-Button Remote Control
Accessory Capacity	40 Remote Controls, 4 Wireless Keyless Entries, 2 Automatic Garage Door Locks (841LM)	12 Remote Controls, 2 Wireless Keyless Entries	40 Remote Controls, 4 Wireless Keyless Entries, 2 Automatic Garage Door Locks (841LM)	40 Remote Controls, 4 Wireless Keyless Entries, 2 Automatic Garage Door Locks (841LM)	40 Remote Controls, 4 Wireless Keyless Entries, 2 Automatic Garage Door Locks (841LM)	24 Remote Controls, 2 Wireless Keyless Entries, 2 Automatic Garage Door Locks (841LM)	24 Remote Controls, 2 Wireless Keyless Entries
Motor Warranty	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime
Parts Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	1 Year	1 Year
Other Warranty	1-Year Battery	1-Year Battery (Optional)	Lifetime Belt, 5-Year LED, 1-Year Battery	Lifetime Belt, 1-Year Battery	-	1-Year Battery	Lifetime Belt

^{*8500} is not compatible with 841LM.

[&]quot;*According to California SB-969, all newly sold or installed garage door openers in residential applications in California need to have battery backup beginning July 1, 2019.

RESIDENTIAL ACCESS SOLUTIONS COMPARISON CHART.

8365W	8160WB	8160W	8165W	8155W	8010
Links					Links
1/2 HP AC			C O N T R A C T (DR SERIES 1/2 HP AC	
Chain Drive Wi-Fi	DC Battery Backup Chain Drive Wi-Fi	DC Chain Drive Wi-Fi	Chain Drive Wi-Fi	Belt Drive Wi-Fi	DC Chain/Cable Drive
Yes	Yes	Yes	Yes	Yes	-
Yes	Yes	Yes	Yes	Yes	-
-	Yes	-	-	-	-
Yes	Yes	Yes	Yes	Yes	Yes
-	Yes 485LM Battery Included	-	-	-	-
	-	-		-	
Front to Back, 2 x 100 Watts	Front, 1x100 Watts	Front, 1 x 100 Watts	Front, 1 x 100 Watts	Front, 1 x 100 Watts	Front, 1 x 60 Watts
-	Yes	Yes	-	-	Yes
-	-	-	-	-	-
T-Rail System	T-Rail System	T-Rail System	T-Rail System	T-Rail System	Square Steel Rail (SSR) System
882LMW Multi-Function Control Panel	882LMW Multi-Function Control Panel	882LMW Multi-Function Control Panel	882LMW Multi-Function Control Panel	882LMW Multi-Function Control Panel	883LM Door Control Button
-	-	-	-	-	-
-	-	-	-	-	-
Yes	Yes	Yes	Yes	Yes	-
893LM 3-Button Remote Control	893LM 3-Button Remote Control	893LM 3-Button Remote Control	893LM 3-Button Remote Control	891LM 1-Button Remote Control	891LM 1-Button Remote Control
24 Remote Controls, 2 Wireless Keyless Entries	12 Remote Controls, 1 Wireless Keyless Entry				
Lifetime	4 Years	4 Years	4 Years	4 Years	1 Year
1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
	4 7 8 11			40 1/ 10 11	

SEAMLESS INTEGRATION.

The right access control solutions for single/multifamily residences and gated communities. Whether it's a single-family home, gated community or larger multifamily building, communities of all sizes count on LiftMaster® to provide trusted and reliable access every day. The LiftMaster suite of products seamlessly work together to confidently manage access for your customers. Plus, all gate operators meet the most stringent UL® safety requirements.





SAFE, SMART TECHNOLOGY FOR SINGLE-FAMILY HOMES.

Choose LiftMaster® and your homebuyers can screen visitors, operate their gate from inside their home and control everything—including their garage door opener—with myQ® on their smartphone.





UNRIVALED PERFORMANCE AND SECURITY FOR MULTIFAMILY DWELLINGS.

Remote programming and expandable access options of myQ® Business™ cloud-based access management software allows full automation across the entire site through multiple entrances.

SECURITY AND CONTROL FOR GATED COMMUNITIES.

Reliable access and expandability for multiple entry points provide the safety and control residential communities desire.



WE PUT SAFETY FIRST.



All LiftMaster Gate Operators meet Underwriters Laboratories' UL® 325 standards for safety and deliver best-in-class performance to keep residents safe. Our Authorized Dealers are trained to properly install our equipment, ensuring you know it will safely work how it should, when it should.

GATE OPERATOR COMPARISON CHART.

LA412PKGUL

RSL12UL

RSW12UL

LA400PKGUL

LA500PKGUL

	LASOUPKGUL	LA400PKGUL	LA412PKGUL	K5L12UL	RSWIZUL
		RESIDI	ENTIAL GATE OPERATOR	s	
Description	24VDC Residential/ Light Commercial Linear Actuator	24VDC Residential Linear Actuator	12VDC Solar Residential Linear Actuator	12VDC Residential/ Light Commercial Slide Gate Operator	12VDC Residential Light Commercial Swing Gate Operator
Battery Backup Powers up when the power's down*	500 Cycles	400 Cycles	Solar	114 Cycles	147 Cycles
Security+ 2.0® 3-Channel Receiver Virtually eliminates interference and extends range	Yes	Yes	Yes	Yes	Yes
myQ® Controls your gate from anywhere with your smartphone	Yes	Yes	Yes	Yes	Yes
Monitored Safety Inputs (Color Coded)	6 Inputs (Main and Expansion Board)	3 Inputs (Main Board)	3 Inputs (Main Board)	3 Inputs (Main Board)	3 Inputs (Main Board)
Exceptional Standby Power**	Up to 24 Days	Up to 97 Days	Up to 126 Days	Up to 63 Days	Up to 63 Days
Best-in-Class Solar Performance*	Approx. 43 Cycles per Day	Approx. 81 Cycles per Day	Approx. 100 Cycles per Day	Approx. 33 Cycles per Day	Approx. 41 Cycles per Day
DC Motor with Smooth Start/Stop	Yes	Yes	Yes	Yes	Yes
Diagnostic Code Display— 2-Digit LED	Yes	Yes	Yes	Yes	Yes
Wireless Dual-Gate Operation	Yes	Yes	Yes	Yes	Yes
Warranty Period	2 Years	2 Years	2 Years	3 Years	3 Years
Max. Gate Length	18 ft.	16 ft.	16 ft.	25 ft.	16 ft.
Max. Gate Weight	1,600 lbs.	850 lbs.	850 lbs.	800 lbs.	1,000 lbs.
Recommended Cycles	300 Cycles per Day	100 Cycles per Day	100 Cycles per Day (See Solar Chart for Specific Details)	120 Cycles per Day	250 Cycles per Day
Power	115V/230V Single Phase	115V Single Phase	Solar Powered Only	115V Single Phase	115V Single Phase
*Cycles noted are for Zone 1 v	with a 10W solar papel (6 hours o	of cuplight per day)			

^{*}Cycles noted are for Zone 1 with a 10W solar panel (6 hours of sunlight per day).
**When installing LMRRUL/LMTBUL, heater option not recommended for solar applications.

GATE OPERATOR COMPARISON CHART.

CSW200UL

SL3000UL

SL585UL

SL595UL

CSW24UL

CSL24UL

HCTDCUL

0011240L	OOLZ-TOL	HOIDOOL	00112000L	OLOGOOOL	OLOGOOL	OLOGOCE
	Total State of the					
ELITE SERIES	S° DC COMMERCIAL GA	TE OPERATORS	ELIT	E SERIES AC COMMERCIA	L/INDUSTRIAL GATE OPER	ATORS
24VDC High-Traffic Commercial Swing Gate Operator	24VDC High-Traffic Commercial Slide Gate Operator	Specialty Overhead Operator	AC Commercial High-Traffic Swing Gate Operator	AC Commercial High-Traffic Slide Gate Operator	AC Industrial Slide Gate Operator	AC Heavy-Duty Industrial Slide Gate Operator
146 Cycles	208 Cycles	112 Cycles	-	-	-	-
Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes	Yes
6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)
Up to 24 Days	Up to 24 Days	Up to 72 Days	-	-	-	-
Approx. 16 Cycles per Day	Approx. 22 Cycles per Day	Approx. 11 Cycles per Day	-	-	-	-
Yes	Yes	Yes	-	-	-	-
Yes	Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes	Yes
7 Years Res. 5 Years Comm.	7 Years Res. 5 Years Comm.	5 Years Comm.	7 Years Res. 5 Years Comm.	7 Years Res. 5 Years Comm.	2 Years	2 Years
18 ft.	50 ft.	16 ft. Door/Gate	1/2 HP 18 ft. 1 HP 22 ft.	1/2 HP 50 ft. 1 HP 50 ft.	1/2 HP 45 ft. 1 HP 70 ft. 1 1/2 HP 75 ft.	1 HP 70 ft. 1 1/2 HP 80 ft. 2 HP 90 ft.
1,600 lbs.	1,500 lbs.	1,000 lbs.	1/2 HP 1,600 lbs. 1 HP 2,000 lbs.	1/2 HP 1,000 lbs. 1 HP 2,000 lbs.	1/2 HP 1,000 lbs. 1 HP 1,600 lbs. 1 1/2 HP 1,900 lbs.	1 HP 1,700 lbs. 1 1/2 HP 2,100 lbs. 2 HP 2,500 lbs.
High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty on 8, 10, 12, 14 and 16 ft. Rails	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	20 Cycles per Hour	25 Cycles per Hour
115V/230V Single Phase	115V/230V Single Phase	115V/230V Single Phase	115V Single Phase	115V Single Phase	115/208/230VAC Single Phase 208/230/460VAC 3 Phase 575VAC 3 Phase	115/208/230VAC Single Phase 208/230/460VAC 3 Phase 575VAC 3 Phase

ACCESS CONTROL COMPARISON CHART.



10", High-Definition TouchscreenCustomize the home screen and quickly search resident names.



Wi-Fi® ConnectivityEasily connect to existing Internet on the property.



Instant Updates

Log in from anywhere with myQ® Business™—no dial-up modems and nothing to download or sync.





	Description	Connected Access Portal, High Capacity
	Remote Programming (Database Matnagement) ally unlimited expansion potential with the freedom to be constantly connected	Yes
	Real-Time Event Monitoring (Email Notifications) Intuitive browser-based interface is easy to use 24/7	Yes
	Cloud Storage Never lose your database	Yes
	Local Event History	50,000
M	aximum Directory Capacity / Programmable Entry Codes	50,000
	Calling Connectivity	Phone.com® Service for Cellular, Wi-Fi®, Wired High-Speed Internet, DSL
	Data Connectivity	Cellular, Wi-Fi, Wired High-Speed Internet, DSL
	Software	myQ® Business™
	Number of Gates/Doors of	
	Control	4
	Wiegand Inputs	4
	Request to Exit	4
	Monitored Input	4
Ado	ditional Gate/Door Expansion	Unlimited (via myQ® Business™)
	Radio Receiver	Security+ 2.0® Passport
	Wiegand Output	1
	Display Type	10 in. 720p High-Def Touch Display
	Postal Lock Provision	Built In
	Camera Ready	Yes
	Mounting Options	Surface, Flush or Gooseneck
	Operating Temperature	-20°F to 130°F (-29°C to 54°C)
	Height	18 in.
	Width	14 in.
	Depth	4.5 in.
	Warranty	2 Years

CAP2D	EL2000SS	EL25G/EL25N/EL25S	EL1SS
			255 m
Connected Access Portal, 2-Door Controller	Telephone Entry/Access Control System	Telephone Entry/Access Control System	Residential Telephone Intercom/ Access Control System
Yes	Yes	Yes	-
Yes	-	-	-
Yes	Yes	Yes	-
6,000	8,000	8,000	-
25,000	2,000	2,000	No Directory/200 Entry Codes
-	POTS/Filtered DSL	POTS/Filtered DSL	Intercom/POTS/Filtered DSL
Cellular, Wired High-Speed Internet, DSL	Dial-Up Modem/Direct Connect/Keypad	Dial-Up Modem/Direct Connect/Keypad	Keypad
myQ® Business™	Versa XS 4.0	Versa XS 4.0	-
BA	SIC INPUT/OUTPUT		
2	4	4	2
2	Up to 4 Wiegand Inputs, with 2 (Optional) Plug-In Modules (WOMODKT)	Up to 4 Wiegand Inputs, with 2 (Optional) Plug-In Modules (WOMODKT)	-
2	4	4	2
2	4	4	-
Unlimited (via myQ® Business™)	Shared Telephone Line for 7 Units	Shared Telephone Line for 7 Units	-
Optional Security+ 2.0 PPWR	Optional Security+ 2.0 PPWR	Optional Security+ 2.0 PPWR	-
-	-	-	-
	PANEL		
Multi-Status LEDs	5" LCD Screen; 4 Display Lines, 20 Characters per Line	Illuminated Keypad	Backlit Keypad/Illuminated Call Button
-	Built In	-	-
-	Yes	Yes	-
Surface/Standard Gang Box	Surface/Flush/Gooseneck	Surface/Gooseneck	Surface/Gooseneck
-31°F to 150°F (-35°C to 66°C)	-4°F to 149°F (-20°C to 65°C)	-4°F to 149°F (-20°C to 65°C)	-4°F to 149°F (-20°C to 65°C)
	16 in.	10.25 in.	6.25 in.
4.5 in.	10 111.		
4.5 in. 3 in.	11.25 in.	6 in.	10 in.
		6 in. 4 in.	10 in. 5.25 in.

SIMPLE, SECURE ACCESS.

Offer homebuyers smart home control with these accessories.

REMOTE LIGHT CONTROL 825LM*

Turns any lamp on and off with a smartphone homebuyers never come home to a dark house.





REMOTE LIGHT SWITCH 823LM*

Replaces an existing wall switch to turn home lighting on and off from your smartphone.

myQ® REMOTE LED LIGHT 827LM

Mounts anywhere in your garage to add bright LED light to any location.





TOOLS AND RESOURCES.

HELP YOUR HOMEBUYER CHOOSE THE RIGHT OPENER AND ACCESSORIES.

For support and imagery to include in your literature, please contact BuilderPrograms@LiftMaster.com.

*Requires a connected myQ account.

ORDER TODAY.



Contact Your LiftMaster® Dealer



Find a Dealer at LiftMaster.com



800.323.2276

© 2019 The Chamberlain Group, Inc. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc.

300 Windsor Drive, Oak Brook, IL 60523

UL® and the UL logo are trademarks of UL LLC © 2018 All Rights Reserved. Wi-Fi® is a registered trademark of Wi-Fi Alliance. LMBDENBR0001PV 5/19

